

SV 450

SV Range: 0.8 GHz - 3.2 GHz / 450 W CW



Prana SV 450

- Class A solid state
- Broadband (instantaneous single band): 0.8 GHz – 3.2 GHz
- Typical output power : 450 W CW
- Linear output power guaranteed with harmonics < -20 dBc
- Air cooling: self contained fans
- Can operate in full mismatch conditions without damage
- Upgradable to SV 1000 possible (30U)
- Reliable, efficient and robust
- 19" cabinet on wheels
- 3 years standard warranty
- Export license can be requested

Maintenance

- Amplifier designed for minimal maintenance
 - Easy access to all parts
 - Modular design
 - Repairs with minimum adjustments
- Rapid diagnostic
- Minimal downtime
- Contract for preventive and corrective maintenance available

Applications

- EMC tests
- RF tests and instrumentation
- Radiocommunication
- Measurement and research laboratories

Versions

- SV 450 DC amplifier with:
 - Display
 - Digital control
 - IEEE 488 GPIB Communication
 - Integrated bidirectional coupler
 - Display of instantaneous power

SV Range

- SV 28 => 28 W CW
- SV 48 => 48 W CW
- SV 90 => 90 W CW
- SV 120 => 120 W CW
- SV 220 => 220 W CW
- SV 450 => 450 W CW
- SV 1000 => 1000 W CW


Extra

- External coupler
- RF Power cable
- Switching unit

SV 450

SV Range: 0.8 GHz - 3.2 GHz / 450 W CW

SV450 POWER AMPLIFIER 450W / 800 MHz - 3200 MHz



Specifications

Frequency bandwidth	0.8 GHz - 3.2 GHz
Typical output power	450 W
Power at 3 dB compression	420 W min. up to 1.8 GHz / 340 W min. from 1.8 GHz to 3.2 GHz
Power at 1 dB compression	300 W min. up to 1.8 GHz / 250 W min. from 1.8 GHz to 3.2 GHz
Harmonics distortion	H2,H3 < -20 dBc for the output power at 1 dB compression
Class type	Class A
Gain	57 dB
Linear power gain flatness	± 5 dB max
Mismatch tolerance	infinite without damage
Input impedance	50 ohms / VSWR: 2:1 max
Output impedance	50 ohms / VSWR: 2:1 max
Input power	+10 dBm max.
RF input connector	Type N fem. (front or rear panel) – other connector type on request
RF output connector	Type 7/16 fem. (front or rear panel) – other connector type on request
Integrated bidirectional power coupler	Coupling factor 69 dB typ.
Power coupling connector	Type N fem. (rear panel)
Safety interlock	Connector type BNC
Digital control	Transistors, power supplies and internal temperature
Mismatch protection	Self limitation for reflected power > 500 W
Communication interface	IEEE 488
4 lines digital display	Status, faults, (direct and reverse instantaneous power for DC version)
Ambient operating temperature	0 °C / + 35 °C
Room temperature storage	-20 °C / +70 °C
Cooling	Forced air: 240 l/sec max. (self contained fans)
Mains voltage	47-63 Hz, 3 phases (star or delta)
Rated current	4 kVA
Dimensions	600 x 840 x 1050 mm (18U) / 23.6 x 33.1 x 41.3 in (18U)
Weight	230 kg / 506 lb

SV45002DEC2024 - Electrical and Mechanical Specifications subject to change without notice.